

<p>代表产品 图片 Pictorial</p> <p>技术参数 Technical</p>	<p>(径向) 电接点 双金属温度计 (Bottom Connection) Electric Contact Bimetallic Thermometer</p> 	<p>(轴向) 普通型双金属温度计 (Back Connection) General Service Bimetallic Thermometer</p> 
<p>产品型号 Model</p>	<p>TWX-41()</p>	<p>TW-30()</p>
<p>公称直径 Diameter</p>	<p>φ100mm</p>	<p>φ76mm</p>
<p>测量精度 Accuracy</p>	<p>1% ; 1.5%</p>	<p>2.5%</p>
<p>测量范围 Range</p>	<p>0 ~ 100</p>	<p>0 ~ 300</p>
<p>仪表外壳 Enclosure</p>	<p>内卡罩壳结构 SUS304, inside bayonet bezel</p>	<p>08F 外卡式罩壳结构 ; 压紧式罩壳结构 08F, bayonet bezel, hermetically sealed bezel</p>
<p>接介材料 Wetted Parts</p>	<p>可选 1cr18Ni9Ti (SUS304; SUS316; SUS316L) optional 1cr18Ni9Ti (SUS304; SUS316; SUS316L)</p>	<p>铜合金 copper alloy</p>
<p>接口尺寸 Connection</p>	<p>M20 × 1.5 / 或其它标准螺纹 M20 × 1.5 or other connection</p>	<p>G1/2</p>
<p>探杆尺寸 Stem</p>	<p>φ12mm; φ6.35mm; φ8mm; φ10mm</p>	<p>φ6.35</p>
<p>特殊说明 Remark</p>	<p>继电器的选用 : - 220V 140mA 30.8W - 220V 140mA 30.8W 单上限,双上限,上下限,双下限,单下限 single upper limit, double upper limit, upper- lower limit, double lower limit, single limit</p>	<p>探杆压铆工艺 riveted stem</p>
<p>外型图 Dimensions</p>		